

TXS-875HT

Order No. 0255340

Hand-held microphone with integrated multi-frequency transmitter, with UHF PLL technology.

- Dynamic microphone cartridge, hypercardioid polar pattern
- Diecast aluminium body
- 193 selectable UHF frequencies (518-542 MHz)
- Adjustable sensitivity (0 dB, -10 dB, -20 dB, -30 dB)
- LCD for indicating frequency and battery status
- Transmitting power: 10 mW (EIRP)
- Selectable lock mode
- Power supply via 2 x 1.5 V battery AA size (not supplied)
- Supplied with plastic case, microphone holder and 7 coloured caps to be pushed on

Model	TXS-875HT
Polar pattern	hypercardioid
System	dynamic
Carrier frequency range	518-542 MHz
Transmitting power	10 mW
Power supply	2 x 1.5 batt. AA size
Operating time	> 30 h
Audio frequency range	50-16,000 Hz
Dimensions	Ø 50 mm x 260 mm
Weight	350 g

Replacement cartridge available:

MD-872: condenser cartridge with an even more brilliant sound, supercardioid polar pattern



TXS-875HSE

Order No. 0255330

Multifrequency pocket transmitter, with UHF PLL technology.

- Suitable for combination with headband microphone or earband microphone with 3-pole mini XLR connector
- 193 selectable UHF frequencies (518-542 MHz)
- Adjustable sensitivity
- LCD for indicating frequency and battery status
- Transmitting power: 10 mW (EIRP)
- Selectable lock mode
- Power supply via 2 x 1.5 V battery AA size (not supplied)
- Supplied in a plastic case

Model	TXS-875HSE
Carrier frequency range	518-542 MHz
Audio frequency range	40-18,000 Hz
Operating time	> 30 h
Admiss. ambient temp.	0-40 °C
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Dimensions transmitter	78 x 190 x 34 mm
Weight transmitter	160 g
Connections transmitter	1 x 3-pole mini XLR



TXS-875

Order No. 0255320

Multifrequency receiver unit, with UHF PLL technology.

- 193 selectable UHF frequencies (518-542 MHz)
- True diversity system with removable antennas (BNC connection)
- Auto-scan
- Pilot tone squelch, noise mute
- Selectable lock mode
- LCD for indicating frequency, antenna A/B, RF receiving level, AF audio level, battery status of the transmitter
- XLR output and 6.3 mm output
- Supplied with power supply
- Supplies operating voltage to TXS-875B

Model	TXS-875
Carrier frequency range	518-542 MHz
Audio frequency range	40-18,000 Hz
THD	< 0.6%
Dynamic range	> 105 dB
Admiss. ambient temp.	0-40 °C
Audio signal receiver	900 mW/1 kΩ (jack) 150 mW/150 Ω (XLR, bal.)
Power supply receiver	via encl. power supply
Dimensions receiver	211 x 40 x 130 mm
Weight receiver	1.1 kg
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.



There are restrictions or requirements in the EU!

Please read the notes on wireless systems in the section "IMPORTANT INFORMATION"!