

## Performer Line

### RU-8011DB/5

Order No. 0259200

#### Diversity UHF PLL wideband receiver

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Removable antennas (BNC connection)
- Auto-scan function
- Pilot tone squelch and noise mute

Model	RU-8011DB/5
Description	receiver unit
Carrier frequency range	506-542 MHz
Audio frequency range	50-16,000 Hz
THD	< 0.6%
Dynamic range	> 105 dB
Audio signal receiver	630 mV/600 Ω XLR (line), 63 mV/600 Ω XLR (mic), 320 mV/600 Ω jack
Power supply receiver	via encl. power supply
Dimensions receiver	210 x 40 x 185 mm
Weight receiver	457 g
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.



### RU-8011D/5

Order No. 0259848

#### Diversity UHF PLL wideband receiver

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels (114 channels)
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Auto-scan function
- Pilot tone squelch and noise mute

Model	RU-8011D/5
Description	receiver unit
Carrier frequency range	506-542 MHz
Audio frequency range	60-15,000 Hz
THD	< 0.6%
Dynamic range	> 105 dB
Audio signal receiver	630 mV/600 Ω XLR (line), 63 mV/600 Ω XLR (mic), 320 mV/600 Ω jack
Power supply receiver	via encl. power supply
Dimensions receiver	210 x 40 x 180 mm
Weight receiver	440 g
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.



### RU-8012DB/5

Order No. 0259420

#### 2-channel diversity UHF PLL wideband receiver

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Removable antennas (BNC connection)
- Auto-scan function
- Pilot tone squelch and noise mute

Model	RU-8012DB/5
Description	receiver unit
Carrier frequency range	506-542 MHz
Audio frequency range	50-16,000 Hz
THD	< 0.6%
Dynamic range	> 105 dB
Audio signal receiver	630 mV/600 Ω XLR (line), 63 mV/600 Ω XLR (mic), 320 mV/600 Ω jack
Power supply receiver	via encl. power supply
Dimensions receiver	210 x 40 x 185 mm
Weight receiver	508 g
Connections receiver	2 x XLR, bal., 2 x 6.3 mm jack, unbal.



### 850CH-2

Order No. 0259370

**Charging station**, for transmitters RU-850LTH/5, RU-850LTB/5 and R-4THA/5.

- For simultaneously charging rech. batteries of 2 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 5 hours
- Each slot with LED for indicating a fault and battery charging status
- Mechanical reverse polarity protection
- Protection against overload, short-circuit and deep discharge

Model	850CH-2
Description	charging station
Colour	black
Suitable for	transmitters RU-850LTH/5, RU-850LTB/5, R-4THA/5
Power supply	via encl. power supply
Dimensions	165 x 72 x 99 mm
Weight	329 g

- Power is provided via enclosed power supply

- Dimensions: 165 x 72 x 99 mm

**Supplied w/o devices.**

